

V-30/HP-600 VIBRATORY DRIVER/EXTRACTOR



HAMMER

DRIVING FORCE	180 tons	1,602 kN
FREQUENCY	1,700 CPM	
ECCENTRIC MOMENT	4,400 in-lbs.	5,078 kg-cm
AMPLITUDE	1 in.	25.4 mm
CLAMPING FORCE	100 tons	890 kN
MAX. LINE PULL	80 tons	712 kN
HEIGHT	136 in.	3,454 mm
THROAT WIDTH	13 in.	330 mm
SHIPPING WIDTH	102 in.	2,591 mm
WEIGHT W/ CLAMP	15,000 lbs.	6,805 kg
HOSE BUNDLE LENGTH	150 ft.	46 m

V-30

POWER UNIT

ENGINE HP	600 HP	446 kW
OPERATING SPEED	1,950 RPM	
HYD. FLOW	180 GPM	684 lpm
HYD. PRESSURE	5,000 psi	345 bar
LENGTH	176 in.	4,470 mm
WIDTH	68 in.	1,727 mm
HEIGHT	90 in.	2,286 mm
WEIGHT	17,000 lbs.	7,738 kg

HP-600



MANUFACTURING, INC.

1198 Pershall Road
St. Louis, MO 63137
(314) 388-2254

www.mktpileman.com

Email: info@mktpileman.com

MKT Manufacturing, Inc. reserves the right to amend these specifications at any time without notice. The only warranty is our standard written warranty. We make no other warranty, expressed or implied.